

HARDSCAPE PORCELAIN

TEHNIČKE KARAKTERISTIKE TECHNICAL FEATURES CARATTERISTICHE TECNICHE

Proizvod, Product, Prodotto: Cemento Dolomiti

Rev: 15/09/2020

OSOBINE FEATURE CARATTERISTICA		TEHNIČKE KARAKTERISTIKE TECHNICAL FEATURES CARATTERISTICHE TECNICHE	NORMA STANDARD NORMA	DOPUŠTENA ODSTUPANJA ESTABLISHED LIMITS LIMITI PREVISTI	CEMENTO DOLOMITI
OBLIK I DIMENZIJE REGULARITY REGOLARITÀ		Dužina i širina Lenght and width Lunghezza e larghezza	ISO 10545-2	± 0.6 %	Zadovoljava Complying Conforme
		Debljina Thickness Spessore	ISO 10545-2	± 5.0 %	Zadovoljava Complying Conforme
		Okomitost Rectangularity Ortogonalità	ISO 10545-2	± 0.6 %	Zadovoljava Complying Conforme
		Ravnost stranica Straightness of sides Rettilineità degli spigoli	ISO 10545-2	± 0.5 %	Zadovoljava Complying Conforme
		Površinska ravnost Surface flatness Planarità	ISO 10545-2	± 0.5 %	Zadovoljava Complying Conforme
STRUKTURNE OSOBINE STRUCTURAL STRUTTURALE		Upijanje vode Water absorption Assorbimento d'acqua	ISO 10545-3	≤ 0.5 %	Zadovoljava Complying Conforme
		Sila loma Breaking strenght Sforzo di rottura	ISO 10545-4	≥ 1300 N	> 11000 N
		Čvrstoća Modulus of rupture Modulo di rottura	ISO 10545-4	≥ 35 N/mm ²	> 45 N/mm ²
	Sila loma klasa Breaking load class Classe di carico di rottura	EN 1339	Deklarirana vrijednost Value declared Valore dichiarato	U11	
TOPLINSKA DJELOVANJA THERMAL HYGROMETRIC TERMO IGROMETRICHE		Otpornost na toplinske udare Thermal shock resistance Resistenza agli sbalzi termici	ISO 10545-9	Zadovoljava Complying Conforme	Zadovoljava Complying Conforme
		Otpornost na smrzavanje Frost resistance Resistenza al gelo	ISO 10545-12	Test Položen Test Passed Test Superato	Zajamčen Guaranteed Garantito

HARDSCAPE PORCELAIN

TEHNIČKE KARAKTERISTIKE TECHNICAL FEATURES CARATTERISTICHE TECNICHE

KEMIJSKE OSOBINE CHEMICAL CHIMICA		Otpornost na mrlje Resistance to stains Resistenza alle macchie	ISO 10545-14	≥ 3	5
		Otpornost na kemikalije (kiseline, baze, soli) Resistance to chemicals (Acids, bases and salts) Resistenza all'attacco chimico (Acidi, basi e sali)	ISO 10545-13	UB minimalan UB MINIMUM UB MINIMO	UA ULA UHA
		Sadržaj olova i kadmija Content of lead and cadmium Contenuto di piombo e cadmio	ISO 10545-15	Deklarirana vrijednost	Ne sadrži Absent Assente
SIGURNOST SAFETY SICUREZZA		Otpornost na klizanje Skid resistance Resistenza allo scivolamento	DIN 51130	Deklarirana vrijednost Value declared Valore dichiarato	R11

U skladu sa normom EN 14411 (ISO 13006) Dodatak G skupina Bla
Compliant with standards EN 14411 (ISO 13006) annex G group Bla
Conforme alla norma EN 14411 (ISO 13006) Appendice G gruppo Bla